

SLK
171

Installations Instruction

DJH - Overroll-Bars



1) Includet

- 1 left Roll-Bar
- 1 right Roll-Bar
- 2 Cover
- 1 TÜV-Dokument

2) Need

- 15, 30, 40er Torx and 10er

3) Preparation

Take enough time for installation!

4) Cleaning

Clean stainless steel whit spezial cleaner and polish sometimes.

5) Removal of the original Parts

1. Open the Roof and push seats to front
2. Unscrew the 2 Torx-Screw from the Box (Pic.1), remove Cover (Pic.2), unscrew the 2 10er Screw out (Pic.3) now remove Box
3. Remove the 2 Plastic Screws (Pic.4)
4. Remove the Screw from Triangle (Pic.5)
5. Take off the Seatbelts Covers (Pic.6)
6. Pull Bars-Cover up and remove (Pic.7)
7. Take off the Seatbelts-Holder (Pic. 8)
8. Unscrew all Screws (Pic. 9)
9. To remove the Screw behind the Bars- push the cover back (Pic.10)



6) Installation of new Parts

1. Original Bars out - DJH-Roll-Bars in (Pic.13+14)
2. Adjust the Roll-Bars in to the Cover
3. Remount all formerly taken off parts
4. Adjust the edges carefully into the frame. Use a small Screwdriver!
5. Push the Plate firmly up or down
6. Remove the protections net!
7. It's done! Everything fits!C

